



# ANALYTIC SYSTEMS

Power Conversion Solutions

## DC/AC 3000 Watt PURESINE INVERTER

### MODEL IPSi3600 SERIES



SHOWN WITH OPTIONAL  
OFFLINE UPS AC INPUT

## Description

The IPSi Series of 'Intelligent Pure Sinewave' Inverters are designed specifically for running computers and other sensitive AC loads in rugged mobile and other off-grid environments.

Two standard AC receptacles (circuit breaker protected) plus a dedicated hardwire connection provide for easy connection of loads.

Models are available for 110 or 220 Volts AC Out at 50 or 60 Hz (user selectable), and to operate from 20-45 or 40-80 Volts DC In to cover all standard DC battery voltages from 24 to 64 volts nominal (includes 72V Rail).

Using the free to download 'Power Wizard' software, the user can select output frequency, output voltage and low voltage shutdown parameters from any laptop through the standard usb interface.

## Benefits

- Proven technology
- Rugged & Reliable for years of safe and trouble free operation
- Multiple battery voltages supported by each model

## Options

- CANBUS or RS485 communication option
- Remote Digital Display and Control option
- OFF-Line UPS option

## Design Features

- Pure Sine Wave output – 110 VAC or 220 VAC at 50 or 60 Hz fully regulated output, exactly the same as household AC
- Hard Wire and Plug-In (NEMA 5-20 or Euro CEE 7/7) AC output connections standard
- Extra heavy input filtering to eliminate interference with other equipment sharing the same batteries
- Digital Signal Processor controlled
- State-of-the art MosFet technology for efficient and reliable operation
- Toroidal transformer type output to protect computers and other sensitive equipment from surges and spikes
- ON-OFF switch illuminated by AC output for positive indication of proper operation
- Thermostatically controlled fan
- Programmable low voltage warning and shutdown to protect the batteries
- Over voltage and over temperature warning and shutdown to protect the inverter
- Current Limiting and Short circuit protection
- Isolated input for positive or negative ground operation
- Diagnostic LEDs and Audible Alarm

An ISO9001 and AS9100 Registered Company Battery Chargers • Inverters • Power Supplies • Voltage Converters

8128 River Way, Delta B.C. V4G 1K5 Canada T. 604.946.9981 F. 604.946.9983 TF. 800.668.3884 (US/CANADA)

[www.analysissystems.com](http://www.analysissystems.com)

# DC/AC 3600 Watt PURESINE INVERTER

# MODEL IPSi3600 SERIES

Electrical (Input)		
Nominal (ip)	24, 28, 32 or 36 VDC	48 or 72 VDC
Actual (Vdc)	20 - 45	40 - 80
Input Amps (max)	180	90
Electrical (Output)		
Output Nominal (op)	110	220
Output Volts (AC)	110 ± 10 VAC (user adjustable)	220 ± 20 VAC (user adjustable)
Output Amps	30A (cont) / 36A (peak)	15A (cont) / 18A (peak)
Output Frequency	50.00 or 60.00 Hz ± 0.01 Hz (user selectable)	
Output Distortion	<2% at 3600 Watts into resistive load	
Regulation (Line & Load)	< +/- 2.0%	
Duty Cycle	Continuous 100% for 24 hours per day	
Efficiency	> 90% @ Maximum Output	
Environmental Specification		
Operating Temp. Range	-25°C to +40°C @ maximum output (-40°C Optional)	
Humidity	0 - 95% Relative Humidity (non-condensing) with standard conformal coating	
Audible Noise	34.5 dB @ 3ft	
Typical Service Life	> 10 years (87,600 hrs)	
Isolation	Input to Output, Output to Case & Input to Case 1500 VDC	
Mechanical Specification		
Length	15.6 +/- 0.1 in / 39.7cm +/- 0.3 cm	
Width	12.0 +/- 0.1 in / 30.5cm +/- 0.3 cm	
Height	8.0 +/- 0.1 in / 21.3cm +/- 0.3 cm	
Clearance	1 inch (2.5 cm) all around	
Material	Marine Grade Aluminium	
Finish	Black Anodize / Powder Epoxy Coat	
Fastenings	All 18-8 Stainless Steel	
Weight	69.5 lbs / 31.5 kg	
Connections	DC In – 3/8 x 16 Inch Imperial Threaded Studs c/w nuts AC Out – 2 x 20A 125V NEMA 5-15 receptacles or 2 x 16A 250V CEE 7/7 receptacles with circuit breaker protection, plus one 30A hardwire connection AC In – one 30A hardwire connection	
Warranty	Three years parts and labor	

Note: Specifications are subject to change without notice.



**ANALYTIC SYSTEMS**  
Power Conversion Solutions

An ISO9001 and AS9100 Registered Company Battery Chargers • Inverters • Power Supplies • Voltage Converters

8128 River Way, Delta B.C. V4G 1K5 Canada T. 604.946.9981 F. 604.946.9983 TF. 800.668.3884 (US/CANADA)

[www.analiticsystems.com](http://www.analiticsystems.com)